

CITGO SUPERGARD® MARINE PLUS LOWER UNIT GEAR LUBE



Date 1/09

DESCRIPTION: SUPERGARD MARINE PLUS Lower Unit Gear Lube is formulated specifically for the marine industry. It contains the latest generation of proprietary EP additive system, designed to provide maximum protection against wear, rust, corrosion and deposits.

QUALITIES: This improved gear lubricant, specifically designed for boating applications, offers unmatched protection, surpassing other marine gear lubricants using GL-4 and GL-5 80W-90 technology:

- Superior EP lubrication and corrosion protection in the presence of moisture (fresh and sea water).
- Improved gear protection for shock load conditions encountered with harsh startup engagement, power reversal, and propeller entanglement.

APPLICATIONS: Recommended for use in all outboard and stern drive gear units specifying SAE 90, 80W-90 or 85W-90, including OMC Type "C." Includes MerCruiser, OMC Cobra, Volvo stern drives and Mercury, Evinrude, Johnson, Mariner, Yamaha, Suzuki, and Force outboards.

TYPICAL PROPERTIES:

CITGO SUPERGARD® MARINE PLUS LOWER UNIT GEAR LUBE

SAE Grade	85W-90
Material Code	631515001
Gravity, ASTM D 4052, °API	26.3
Density, lb/gal at 60°F	7.5
Flash Point, ASTM D 92, COC, °F (°C)	420 (216)
Viscosity, cSt at 100°C	16.0
Brookfield Viscosity, -23°C, cP	102,000
Pour Point, ASTM D 97, °F (°C)	-15 (-26)
Channel Point, °F (°C), Max	-31 (-35)
Color, Visual	Blue
Foam Test, ASTM D 892	Pass
Copper Corrosion, 3 hrs at 250°F	Pass