



CITGO NO DRIP OILS

Date 01/08

- DESCRIPTION:** CITGO No Drip Oils are premium quality, tacky-type oils. They are particularly suited for applications where the lubricant must not make contact with the material being processed.
- QUALITIES:** CITGO No Drip Oils are formulated with an ash-free and non-corrosive tackiness agent which reduces lubricant creep and drip tendencies, and stays where applied.
- They provide a high natural detergency, and a low tendency for hard carbon formation, which help keep lubricated parts clean. They provide good seal swell, and good continuous film protection for general lubrication characteristics.
- They are compatible with all types of filtering equipment.
- APPLICATIONS:** CITGO No Drip Oils are recommended for general machinery lubrication, for plain, anti-friction and rolling mill bearings, and for parallel-shaft enclosed gears, where conditions are mild.
- They are widely used for textile machinery, packaging machinery, electric motors, chains, machine tools and general machine lubrication, where tacky oils are desired.
- They can also be used for coating air filters.

**TYPICAL PROPERTIES:**

CITGO NO DRIP OILS		
Iso Vis Grade	100	320
Material Code	637144001	637143001
Gravity, ASTM D 4052, °API	22	21
Flash Point, ASTM D 92, °F	350	430
Viscosity, ASTM D 445, cSt at 40°C	100	320
ASTM D 2161, SUS at 100°F	515	1,700
SUS at 210°F	55	82
Pour Point, ASTM D 97, °F (°C)	-5 (-21)	10 (-12)
Color, ASTM D 1500	2.0	2.5