



C I T G O F O R M - L - 2 2 6

Date 01/08

DESCRIPTION: CITGO Form-L-226 is a heavy duty compounded release agent for metal or wooden forms used in severe service concrete work. Light product color minimizes discoloration of concrete.

QUALITIES: CITGO Form-L-226 Oil is compounded with a release agent to improve separation of forms and molds, a corrosion inhibitor to enhance corrosion protection, and an oiliness agent for ease of spreading. It will displace water from metal surfaces.

CITGO Form-L-226 Oil can be applied by spray, brush, swab, or dipping, and is foam resistant to ensure the integrity of the protective film during pressure spray application.

APPLICATIONS: CITGO Form-L-226 Oil is recommended for coating metal or wooden forms into which concrete is poured under hot arid conditions or difficult or complex concrete pours.

CITGO Form-L-226 Oil can be applied at nominal operating conditions without dilution or heating.

TYPICAL PROPERTIES:**CITGO FORM-L-226**

Iso Vis Grade	22
Material Code	643210001
Gravity, ASTM D 4052, °API	23.8
Flash Point, ASTM D 92, °F	310
Viscosity, ASTM D 445, cSt at 40°C	22
ASTM D 2161, SUS at 100°F	112
Pour Point, ASTM D 97, °F (°C)	-40 (-40)
Color, ASTM D 1500	L1.0