C I T G O G A S C O M® R O I L

Date 1/09

DESCRIPTION: CITGO Gascom R Oil is formulated to satisfy the lubrication requirements of gas compressors used for wet, scrubbed or processed gases.

QUALITIES: CITGO Gascom R Oil is formulated with a high VI base stocks and a special lubricity additive which reduces lubricant displacement by water and/or liquid hydrocarbons.

CITGO Gascom R Oil can tolerate a wide variety of gas quality.

APPLICATIONS: CITGO Gascom R Oil satisfies the lubricant requirements of single or double-acting reciprocating compressors in raw, scrubbed or processed natural gas service.

CITGO Gascom R Oil can also be used as a mild stamping and drawing lubricant where fatty lubricity is needed.

TYPICAL PROPERTIES:

CITGO GASCOM® R OIL	
ISO VIS Grade	**220**
Material Code	637142001
Gravity, ASTM D 4052, °API	27.5
Flash Point, ASTM D 92, °F (°C)	450 (232)
Viscosity, ASTM D 445, cSt at 40°C	255
cSt at 100°C	20
ASTM D 2161, SUS at 100°F	1350
SUS at 210°F	100
Viscosity Index, ASTM D 2270	90
Pour Point, ASTM D 97, °F (°C)	10 (-12)
Color, ASTM D 1500	5.5