



C I T G O F O R M O I L E F

Date 10/06

- DESCRIPTION:** CITGO Form Oil EF is a heavy duty, compounded release agent for metal or wooden forms used in severe service concrete work.
- QUALITIES:** CITGO Form Oil EF is formulated with a Food Grade White Mineral Oil and complimentary additives to produce an environmentally friendly product. It is inherently biodegradeable, non-toxic to aquatic life, will not leave a sheen on the water, and will meet California Standards for VOC.
- CITGO Form Oil EF is essentially water white in color to prevent staining of the concrete pour, and gives improved form and mold separations for use in difficult or complex concrete pours.
- CITGO Form Oil EF is compounded with a release agent to enhance corrosion protection, and an oiliness agent for ease of spreading, and will displace water from metal surfaces.
- CITGO Form Oil EF can be applied by spray, brush, swab, or dipping, and is foam resistant to ensure the integrity of the protective film during pressure spray application.
- APPLICATIONS:** CITGO Form Oil EF is recommended for lubricating metal or wooden concrete forms used in environmentally sensitive areas.
- CITGO Form Oil EF Can be applied at nominal operating conditions without dilution or heating.

TYPICAL PROPERTIES:

CITGO FORM OIL EF

ISO VIS Grade	15
Material Code	643230001
Gravity, ASTM D 4052, °API	33
Flash Point, ASTM D 92, °F	350
Viscosity, ASTM D 445, cSt at 40°C	15
ASTM D 2161, SUS at 100°F	85
Pour Point, ASTM D 97, °F (°C)	+10 (-12)
Color, ASTM D 1500	L0.5