



CITGO LITHOPLEX® CV NO. 2 GREASE

Date 1/09

DESCRIPTION: CITGO Lithoplex CV No. 2 Grease is a premium quality Lithium Complex NLGI No. 2 grease that is fully additive treated to reduce wear, oxidation, and corrosion.

QUALITIES: **Extreme Pressure and Wear Protection:** CITGO Lithoplex CV No. 2 Grease contains additives to minimize wear, even under extreme pressure conditions.

Rust Protection: This product protects equipment against corrosion and passes the ASTM D1743 corrosion resistance test.

Water Resistance: CITGO Lithoplex CV No. 2 Grease is water insoluble and water resistant.

APPLICATIONS: CITGO Lithoplex CV No. 2 Grease is a versatile product that is suitable for a wide variety of industrial, agricultural, mining, construction, trucking, and automotive applications. This product is suitable for use in many CVJ applications. This grease has demonstrated compatibility with many boot materials, however, as in all CVJ applications, the customer should verify that the grease is compatible with the boot material prior to use.

TYPICAL PROPERTIES:

CITGO LITHOPLEX® CV NO. 2 GREASE

NLGI Grade	2
Material Code	655362001
Worked-60 Penetration, ASTM D 217	265 - 295
Grease Type	Lithium Complex
Color	Medium Amber/Brown
Texture	Smooth
Rust Prevention, ASTM D 1743, Rating	Pass
Dropping Point, ASTM D 2265, °F (°C)	500 (260)
Four-Ball Wear, ASTM D 2266, mm scar	0.55
Four-Ball Weld, ASTM D 2596, kgf	315
Four-Ball LWI, ASTM D 2596	50
Base Oil Viscosity cSt. at 100°C	13.0
cSt. at 40°C	162
Viscosity Index	63