



CITGO TRANSGARD® DEXRON®-VI ATF

Date 1/09

DESCRIPTION: CITGO TRANSGARD DEXRON-VI ATF is an automatic transmission fluid approved by General Motors for use in its vehicles with automatic transmissions. This fluid is designed to provide twice the normal service life of a DEXRON-IIIH ATF. It offers enhanced performance for both new and older model transmissions.

- QUALITIES:**
- Extends fluid and transmission life and offers the potential to extend drain intervals
 - Outstanding oxidation life and thermal stability offering resistance to sludge and varnish formation
 - Superior anti-wear protection
 - Improved low temperature viscosity
 - Optimized frictional properties to prevent shudder; and extend fluid and clutch durability
 - Improved fuel economy versus DEXRON-IIIH fluids
 - Increased shear stability

APPLICATIONS: CITGO TRANSGARD DEXRON-VI ATF is recommended for use in automatic transmissions manufactured by General Motors. The product is backward compatible and can be used in all General Motors cars and trucks where DEXRON-III, DEXRON-IIIE and DEXRON-II type fluids were called for. TRANSGARD DEXRON-VI ATF was specifically designed for use in the Hydra-Matic 6-speed transmission.

Do not use DEXRON-VI in applications calling for Ford MERCON®, MERCON V, MERCON SP, or Type F. DEXRON-VI is not suitable for use in non-GM vehicles which called for DEXRON-III or DEXRON-II type fluids. In these applications CITGO recommends the use of TRANSGARD Multi-Purpose ATF.

TYPICAL PROPERTIES:**CITGO TRANSGARD® DEXRON®-VI ATF**

Material Code	633140001
Gravity, ASTM D 4052, °API	35.35
Pounds Per Gallon	7.05
Flash Point, COC, ASTM D 92, °F (°C)	403 (206)
Pour Point, ASTM D 97, °F (°C)	-65 (-54)
Viscosity, ASTM D 445, cSt at 40°C	29.7
cSt at 100°C	6.0
ASTM D 2983, cP at -20°C	1,050
cP at -40°C	12,000
Viscosity Index, ASTM D 2270	150
Color	Red