

# SAFETY DATA SHEET

E85



## Section 1. Identification

**GHS product identifier** : E85  
**Synonyms** : Ethanol with Conventional Unleaded Gasoline  
**Material uses** : Fuel.  
**Code** : 12300  
**MSDS #** : 12300

**Supplier's details** : CITGO Petroleum Corporation  
P.O. Box 4689  
Houston, TX 77210  
sdsvend@citgo.com

**Emergency telephone number (with hours of operation)** : Technical Contact: (800) 248-4684  
Medical Emergency: (832) 486-4700  
CHEMTREC Emergency: (800) 424-9300  
(United States Only)

## Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
GERM CELL MUTAGENICITY - Category 1  
CARCINOGENICITY - Category 1A  
TOXIC TO REPRODUCTION (Unborn child) - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), hearing organs) - Category 2  
AQUATIC HAZARD (ACUTE) - Category 2  
AQUATIC HAZARD (LONG-TERM) - Category 2

### GHS label elements

#### Hazard pictograms



#### Signal word

: Danger

#### Hazard statements

: Highly flammable liquid and vapor.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause genetic defects.  
May cause cancer.  
Suspected of damaging the unborn child.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS), hearing organs)  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### General

: Do not syphon by mouth.

## Section 2. Hazards identification

- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling.
- Response** : Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Do not taste or swallow. Wash thoroughly after handling.
- Hazards not otherwise classified** : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire or explosion. Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Ethanol with Conventional Unleaded Gasoline

### CAS number/other identifiers

- CAS number** : Not applicable.

Ingredient name	%	CAS number
Ethanol	85	64-17-5
Pentanes	1 - 5	109-66-0
Toluene	1 - 5	108-88-3
Xylene	1 - 5	1330-20-7
Hexanes, other isomers	1 - 5	*
Heptane	1 - 5	142-82-5
Benzene	0.1 - 1	71-43-2
Cumene	0.1 - 1	98-82-8
Ethylbenzene	0.1 - 1	100-41-4
Naphthalene	<0.5	91-20-3

\* = Various      \*\* = Mixture      \*\*\* = Proprietary

Any concentration shown as a range is to protect confidentiality or is due to process variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation. Breathing high concentrations can cause irregular heartbeats which can be fatal.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Breathing high concentrations can cause irregular heartbeats which may be fatal. Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination.  
Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

## Section 4. First aid measures

- Notes to physician** : This material (or a component) may sensitize the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material.
- Specific treatments** : Treat symptomatically and supportively.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use caution when applying carbon dioxide in confined spaces.  
SMALL FIRE: Steam, CO<sub>2</sub>, dry chemical or inert gas (e.g., nitrogen). LARGE FIRE: Use foam, water fog or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, ignition or explosion.
- Unsuitable extinguishing media** : Do not use water jet.

### Specific hazards arising from the chemical

- : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static accumulation may be significantly increased by the presence of small quantities of water or other contaminants. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

### Hazardous thermal decomposition products

- : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### Special protective actions for fire-fighters

- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

### Special protective equipment for fire-fighters

- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## Section 6. Accidental release measures

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Restrict flow velocity according to API 2003 (2008), NFPA 77 (2007), and Laurence Britton, "Avoiding Static Ignition Hazards in Chemical Operations". To reduce potential for static discharge, ensure that all equipment is properly grounded and bonded and meets appropriate electrical classification requirements. Non equilibrium conditions may increase the fire hazard associated with this product. Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle. Special precautions, such as reduced loading rates and increased monitoring, must be observed during "switch loading" operations (i.e., loading this material in tanks or shipping compartments that previously contained a dissimilar product).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**Bulk Storage Conditions:** Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

Head spaces in tanks and other containers may contain a mixture of air and vapor in the flammable range. Vapor may be ignited by static discharge. Storage area must meet OSHA requirements and applicable fire codes. Additional information regarding the design and control of hazards associated with the handling and storage of flammable and combustible liquids may be found in professional and industrial documents including, but not limited to, the National Fire Protection Association (NFPA) publications NFPA 30 ("Flammable and Combustible Liquid Code"), NFPA 77 ("Recommended Practice on Static Electricity") and the American Petroleum Institute (API) Recommended Practice 2003, ("Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents").

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ethanol

**ACGIH TLV (United States).**

TWA: 1000 ppm 8 hours.

**ACGIH TLV (United States, 3/2017).**

STEL: 1000 ppm 15 minutes.

**NIOSH REL (United States, 10/2016).**

TWA: 1000 ppm 10 hours.

TWA: 1900 mg/m<sup>3</sup> 10 hours.

**OSHA PEL (United States, 6/2016).**

TWA: 1000 ppm 8 hours.

TWA: 1900 mg/m<sup>3</sup> 8 hours.

Gasoline

**ACGIH TLV (United States, 3/2017).**

TWA: 300 ppm 8 hours.

TWA: 890 mg/m<sup>3</sup> 8 hours.

STEL: 500 ppm 15 minutes.

STEL: 1480 mg/m<sup>3</sup> 15 minutes.

Pentanes

**NIOSH REL (United States, 10/2016).**

TWA: 120 ppm 10 hours.

TWA: 350 mg/m<sup>3</sup> 10 hours.

CEIL: 610 ppm 15 minutes.

CEIL: 1800 mg/m<sup>3</sup> 15 minutes.

**ACGIH TLV (United States, 3/2017).**

TWA: 1000 ppm 8 hours.

**OSHA PEL (United States, 6/2016).**

TWA: 1000 ppm 8 hours.

TWA: 2950 mg/m<sup>3</sup> 8 hours.

Toluene

**OSHA PEL Z2 (United States, 2/2013).**

TWA: 200 ppm 8 hours.

CEIL: 300 ppm

AMP: 500 ppm 10 minutes.

**NIOSH REL (United States, 10/2016).**

TWA: 100 ppm 10 hours.

TWA: 375 mg/m<sup>3</sup> 10 hours.



## Section 8. Exposure controls/personal protection

Xylene	<p>STEL: 150 ppm 15 minutes.            STEL: 560 mg/m<sup>3</sup> 15 minutes.  <b>ACGIH TLV (United States, 3/2017).</b>            TWA: 20 ppm 8 hours.  <b>ACGIH TLV (United States, 3/2017).</b>            TWA: 100 ppm 8 hours.            TWA: 434 mg/m<sup>3</sup> 8 hours.            STEL: 150 ppm 15 minutes.            STEL: 651 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL (United States, 6/2016).</b>            TWA: 100 ppm 8 hours.            TWA: 435 mg/m<sup>3</sup> 8 hours.</p>
Hexanes, other isomers	<p><b>ACGIH TLV (United States).</b>            TWA: 500 ppm 8 hours.            STEL: 1000 ppm 15 minutes.</p>
Heptane	<p><b>ACGIH TLV (United States, 3/2017).</b>            TWA: 400 ppm 8 hours.            TWA: 1640 mg/m<sup>3</sup> 8 hours.            STEL: 500 ppm 15 minutes.            STEL: 2050 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2016).</b>            TWA: 85 ppm 10 hours.            TWA: 350 mg/m<sup>3</sup> 10 hours.            CEIL: 440 ppm 15 minutes.            CEIL: 1800 mg/m<sup>3</sup> 15 minutes.  <b>OSHA PEL (United States, 6/2016).</b>            TWA: 500 ppm 8 hours.            TWA: 2000 mg/m<sup>3</sup> 8 hours.</p>
Benzene	<p><b>ACGIH TLV (United States, 3/2017).</b>  <b>Absorbed through skin.</b>            TWA: 0.5 ppm 8 hours.            TWA: 1.6 mg/m<sup>3</sup> 8 hours.            STEL: 2.5 ppm 15 minutes.            STEL: 8 mg/m<sup>3</sup> 15 minutes.  <b>NIOSH REL (United States, 10/2016).</b>            TWA: 0.1 ppm 10 hours.            STEL: 1 ppm 15 minutes.  <b>OSHA PEL (United States, 6/2016).</b>            TWA: 1 ppm 8 hours.            STEL: 5 ppm 15 minutes.  <b>OSHA PEL Z2 (United States, 2/2013).</b>            TWA: 10 ppm 8 hours.            CEIL: 25 ppm            AMP: 50 ppm 10 minutes.</p>
Cumene	<p><b>NIOSH REL (United States, 10/2016).</b>  <b>Absorbed through skin.</b>            TWA: 50 ppm 10 hours.            TWA: 245 mg/m<sup>3</sup> 10 hours.  <b>ACGIH TLV (United States, 3/2017).</b>            TWA: 50 ppm 8 hours.  <b>OSHA PEL (United States, 6/2016).</b>  <b>Absorbed through skin.</b>            TWA: 50 ppm 8 hours.            TWA: 245 mg/m<sup>3</sup> 8 hours.</p>
Ethylbenzene	<p><b>ACGIH TLV (United States, 3/2017).</b>            TWA: 20 ppm 8 hours.  <b>NIOSH REL (United States, 10/2016).</b>            TWA: 100 ppm 10 hours.            TWA: 435 mg/m<sup>3</sup> 10 hours.            STEL: 125 ppm 15 minutes.            STEL: 545 mg/m<sup>3</sup> 15 minutes.</p>

## Section 8. Exposure controls/personal protection

Naphthalene

**OSHA PEL (United States, 6/2016).**

TWA: 100 ppm 8 hours.

TWA: 435 mg/m<sup>3</sup> 8 hours.

**ACGIH TLV (United States). Absorbed through skin.**

STEL: 15 ppm 15 minutes.

**ACGIH TLV (United States, 3/2017).**

**Absorbed through skin.**

TWA: 10 ppm 8 hours.

TWA: 52 mg/m<sup>3</sup> 8 hours.

**NIOSH REL (United States, 10/2016).**

TWA: 10 ppm 10 hours.

TWA: 50 mg/m<sup>3</sup> 10 hours.

STEL: 15 ppm 15 minutes.

STEL: 75 mg/m<sup>3</sup> 15 minutes.

**OSHA PEL (United States, 6/2016).**

TWA: 10 ppm 8 hours.

TWA: 50 mg/m<sup>3</sup> 8 hours.

**Appropriate engineering controls**

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls**

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures**

**Hygiene measures**

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection**

- : Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.

**Skin protection**

**Hand protection**

- : Avoid skin contact with liquid. Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Heavy duty, industrial grade chemically resistant gloves constructed of nitrile, neoprene, polyethylene, fluoroelastomer rubber or polyvinyl chloride as approved by glove manufacturer. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Leather gloves are not protective for liquid contact.

**Body protection**

- : Avoid skin contact with liquid. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection**

- : Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.



## Section 8. Exposure controls/personal protection

- Respiratory protection** : Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If an air purifying respirator is appropriate, use one equipped with cartridges rated for organic vapors.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Transparent, clear to amber
- Odor** : Pungent, characteristic gasoline.
- pH** : Not available.
- Boiling point** : 38 to 204°C (100.4 to 399.2°F)
- Flash point** : Closed cup: -43°C (-45.4°F) [Tagliabue [ASTM D-56]]
- Evaporation rate** : 7.5 (n-butyl acetate. = 1)
- Lower and upper explosive (flammable) limits** : Lower: 1.4%  
Upper: 7.6%
- Vapor pressure** : 1.5 kPa (11.5 mm Hg) [room temperature]
- Vapor density** : 3 [Air = 1]
- Relative density** : 0.745
- Density lbs/gal** : Estimated 6.21 lbs/gal
- Density gm/cm<sup>3</sup>** : Not available.
- Gravity, °API** : Estimated 58 @ 60 F
- Solubility** : Very slightly soluble in the following materials: cold water.
- Auto-ignition temperature** : 280°C (536°F)
- Flow time (ISO 2431)** : Not available.
- Viscosity** : Kinematic (room temperature): <0.01 cm<sup>2</sup>/s (<1 cSt)
- Conductivity** : <50 picosiemens/meter (unadditized)

## Section 10. Stability and reactivity

- Reactivity** : Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. Do not store with strong oxidizing agents.
- Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	LC50 Inhalation Vapor	Mouse	>40000 ppm	10 minutes
	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Guinea pig	5560 mg/kg	-
	LD50 Oral	Rabbit	6300 mg/kg	-
Gasoline	LD50 Oral	Rat	7060 mg/kg	-
	LD50 Oral	Rat	13.6 g/kg	-
Toluene	LC50 Inhalation Vapor	Rat	>20 mg/l	4 hours
	LD50 Dermal	Rabbit	12267 mg/kg	-
	LD50 Oral	Rat - Male	5580 mg/kg	-
	TDL <sub>o</sub> Oral	Rat	0.65 g/kg	-
Xylene	TDL <sub>o</sub> Oral	Rat	1000 mg/kg	-
	LC50 Inhalation Vapor	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	6700 ppm	4 hours
	LD50 Oral	Mouse	2119 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
Hexanes, other isomers	LD50 Oral	Rat	4300 mg/kg	-
	LC50 Inhalation Vapor	Rat	48000 ppm	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
Heptane	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	10000 ppm	7 hours
Benzene	LD50 Oral	Mammal - species unspecified	5700 mg/kg	-
	LD50 Oral	Mouse	4700 mg/kg	-
Cumene	LD50 Oral	Rat	6400 mg/kg	-
	LC50 Inhalation Vapor	Mouse	10 g/m <sup>3</sup>	7 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
Ethylbenzene	LD50 Oral	Rat	4000 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
Naphthalene	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Oral	Rat	490 mg/kg	-

**Conclusion/Summary** : **ethanol**: Inhalation exposure to ethanol vapor at concentrations above applicable workplace exposure levels is expected to produce eye and mucus membrane irritation. Human exposure at concentrations from 1000 to 5000 ppm produced symptoms of narcosis, stupor and unconsciousness. Subjects exposed to ethanol vapor in concentrations between 500 and 10,000 ppm experienced coughing and smarting of the eyes and nose. At 15,000 ppm there was continuous lacrimation and coughing. While extensive acute and chronic effects can be expected with ethanol consumption, ingestion is not expected to be a significant route of exposure to this product.

**pentane**: Studies of pentane isomers in laboratory animals indicate exposure to extremely high levels (roughly 10 vol.%) may induce cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

**toluene**: Deliberate inhalation of toluene at high concentrations (e.g., glue sniffing and solvent abuse) can cause CNS depression, cardiac arrhythmias and death.

**xylene**: Overexposure to xylene may cause upper respiratory tract irritation, headache, cyanosis, blood serum changes, CNS damage and narcosis. Effects may be increased by the use of alcoholic beverages. Evidence of liver and kidney impairment were reported in workers recovering from a gross over-exposure.

**heptane**: Heptane is a CNS depressant and narcosis at elevated concentrations.

#### Irritation/Corrosion

## Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
Xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Benzene	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Moderate irritant	Rabbit	-	88 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
Cumene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Eyes - Mild irritant	Rabbit	-	86 milligrams	-
Ethylbenzene	Skin - Mild irritant	Rabbit	-	24 hours 10 milligrams	-
Naphthalene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
				495 milligrams	-

**Skin** : **xylene**: May cause skin irritation.  
**Eyes** : **xylene**: May cause eye irritation.  
**Respiratory** : **xylene**: May cause respiratory irritation.

### Sensitization

Not available.

**Skin** : **toluene**: Non-sensitizer to skin.  
**Respiratory** : **toluene**: Non-sensitizer to lungs.

### Mutagenicity

Not available.

**Conclusion/Summary** : **heptane**: n-heptane was not mutagenic in the Salmonella/microsome (Ames) assay.

### Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene	Positive - Inhalation - TD	Rat - Female	-	-

**Conclusion/Summary** :

## Section 11. Toxicological information

**ethanol:** IARC Monograph 96 (2010) identified Ethanol in alcoholic beverages as a Group 1 carcinogen.

**Gasoline:** IARC has determined that gasoline and gasoline exhaust are possibly carcinogenic to humans. Exposure to wholly vaporized unleaded gasoline was associated with kidney cancers in male rats and liver tumors in female mice. The male rat kidney tumors are specific to that species and are not relevant to human health. The significance of the tumors identified in female mice is unclear.

### Classification

Product/ingredient name	OSHA	IARC	NTP
Ethanol	-	1	-
Toluene	-	3	-
Xylene	-	3	-
Benzene	+	1	Known to be a human carcinogen.
Cumene	-	2B	Reasonably anticipated to be a human carcinogen.
Ethylbenzene	-	2B	-
Naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.

### Reproductive toxicity

Not available.

**Conclusion/Summary :** **toluene:** Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Several studies of workers suggest long-term exposure may be related to small increases in spontaneous abortions and changes in some gonadotropic hormones. However, the weight of evidence does not indicate toluene is a reproductive hazard to humans. Studies in laboratory animals indicate some changes in reproductive organs following high levels of exposure, but no significant effects on mating performance or reproduction were observed. Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Findings in laboratory animals were largely negative. Positive findings include small increases in minor skeletal and visceral malformations and developmental delays following very high levels of maternal exposure.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene	Negative - Inhalation	Rat	-	-

**Conclusion/Summary :** No additional information.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Ethanol	Category 3	Not applicable.	Respiratory tract irritation
Pentanes	Category 3	Not applicable.	Narcotic effects
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Hexanes, other isomers	Category 3	Not applicable.	Narcotic effects
Heptane	Category 3	Not applicable.	Narcotic effects
Cumene	Category 3	Not applicable.	Respiratory tract irritation
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Toluene	Category 2	Inhalation	central nervous system (CNS)
Xylene	Category 2	Not determined	hearing organs
Benzene	Category 1	Inhalation	blood system

### Aspiration hazard

Name	Result
Gasoline	ASPIRATION HAZARD - Category 1
Pentanes	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1
Hexanes, other isomers	ASPIRATION HAZARD - Category 1
Heptane	ASPIRATION HAZARD - Category 1
Benzene	ASPIRATION HAZARD - Category 1
Cumene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation. Breathing high concentrations can cause irregular heartbeats which can be fatal.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : Corrosive to the digestive tract. Causes burns.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Breathing high concentrations can cause irregular heartbeats which may be fatal. Repeated or prolonged overexposure to solvents can cause brain or other nervous system damage. The symptoms can include the loss of memory, the loss of intellectual capacity and the loss of coordination. Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

## Section 11. Toxicological information

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**General** : May cause damage to organs through prolonged or repeated exposure.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : May cause genetic defects.

**Teratogenicity** : Suspected of damaging the unborn child.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 µl/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
Toluene	Chronic NOEC 0.375 µl/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
Xylene	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Heptane	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute EC50 1.5 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 4 mg/l	Fish - Carassius auratus	24 hours
	Acute LC50 375000 µg/l Fresh water	Fish - Oreochromis mossambicus	96 hours
Benzene	Acute LC50 4924 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
	Acute EC50 29000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1600000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute EC50 9230 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 21 mg/l Marine water	Crustaceans - Artemia salina	48 hours



## Section 12. Ecological information

Cumene	Acute LC50 5.28 ul/L Fresh water	Fish - Oncorhynchus gorboscha - Fry	96 hours
	Chronic EC10 >1360 mg/l Fresh water	Algae - Scenedesmus subspicatus	96 hours
	Chronic NOEC 98 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 1.5 to 5.4 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Wearling)	4 weeks
	Acute EC50 2600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Ethylbenzene	Acute EC50 7400 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 10600 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
Naphthalene	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2350 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
E85	Acute LC50 213 µg/l Fresh water	Fish - Melanotaenia fluviatilis - Larvae	96 hours
	Chronic NOEC 0.5 mg/l Marine water	Crustaceans - Uca pugnax - Adult	3 weeks
	Chronic NOEC 1.5 mg/l Fresh water	Fish - Oreochromis mossambicus	60 days
	LC50 100 mg/l	Fish	96 hours

**Conclusion/Summary** : Not available.

### Persistence and degradability

**Conclusion/Summary** : **toluene**: Rapidly biodegradable in aerobic conditions.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
Benzene	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Ethanol	-0.35	-	low
Gasoline	2 to 7	10 to 2500	high
Pentanes	3.45	171	low
Toluene	2.73	90	low
Xylene	3.12	8.1 to 25.9	low
Heptane	4.66	552	high
Benzene	2.13	11	low
Cumene	3.55	35.48	low
Ethylbenzene	3.6	-	low
Naphthalene	3.4	36.5 to 168	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

### Disposal methods





: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**RCRA classification** : D001, D018

### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Toluene; Benzene, methyl-Xylene	108-88-3 1330-20-7	Listed Listed	U220 U239

## Section 14. Transport information

	DOT Classification	IMDG	IATA
<b>UN number</b>	UN3475	UN3475	UN3475
<b>UN proper shipping name</b>	Ethanol and Gasoline Mixture	ETHANOL AND GASOLINE MIXTURE	Ethanol and Gasoline Mixture
<b>Transport hazard class(es)</b>	3 	3  	3 
<b>Packing group</b>	II	II	II
<b>Environmental hazards</b>	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.

### Additional information

#### DOT Classification

: **Limited quantity** Yes.  
**Packaging instruction** Exceptions: 150. Non-bulk: 202. Bulk: 242.  
**Quantity limitation** Passenger aircraft/rail: 5 L. Cargo aircraft: 60 L.  
**Special provisions** 144, 177, IB2, T4, TP1

#### TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.

#### ADR/RID

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

#### IMDG

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Emergency schedules** F-E, S-E  
**Special provisions** 333, 363

## Section 14. Transport information

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.  
**Quantity limitation** Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.  
**Special provisions** A156

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Water Act (CWA) 307:** toluene; benzene; ethylbenzene; naphthalene  
**Clean Water Act (CWA) 311:** toluene; xylene; benzene; ethylbenzene; cyclohexane; naphthalene  
 This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.  
**Clean Air Act (CAA) 112 regulated flammable substances:** pentane

### SARA 302/304

#### Composition/information on ingredients

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : FLAMMABLE LIQUIDS - Category 2  
 SKIN IRRITATION - Category 2  
 EYE IRRITATION - Category 2A  
 GERM CELL MUTAGENICITY - Category 1  
 CARCINOGENICITY - Category 1A  
 TOXIC TO REPRODUCTION (Unborn child) - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), hearing organs) - Category 2  
 HNOC - Static-accumulating flammable liquid  
 HNOC - Corrosive to digestive tract

#### Composition/information on ingredients

Name	%	Classification
Ethanol	≥75 - ≤90	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Gasoline	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 1 GERM CELL MUTAGENICITY - Category 1B CARCINOGENICITY - Category 1B ASPIRATION HAZARD - Category 1
Pentanes	≤3	FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

## Section 15. Regulatory information

Toluene	≤3	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE LIQUIDS - Category 2          SKIN IRRITATION - Category 2          EYE IRRITATION - Category 2A          TOXIC TO REPRODUCTION (Unborn child) - Category 2          SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3          SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3          SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2          SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS)) (inhalation) - Category 2</p>
Xylene	≤3	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE LIQUIDS - Category 3          ACUTE TOXICITY (inhalation) - Category 4          SKIN IRRITATION - Category 2          EYE IRRITATION - Category 2A          SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2</p>
Hexanes, other isomers	≤3	<p>FLAMMABLE LIQUIDS - Category 2          SKIN IRRITATION - Category 2          TOXIC TO REPRODUCTION (Fertility) (inhalation) - Category 2          SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3</p>
Heptane	≤3	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE LIQUIDS - Category 2          SKIN IRRITATION - Category 2          SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3</p>
Benzene	<1	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE LIQUIDS - Category 2          SKIN IRRITATION - Category 2          EYE IRRITATION - Category 2A          GERM CELL MUTAGENICITY - Category 1B          CARCINOGENICITY - Category 1A          SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1          SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (blood system) (inhalation) - Category 1</p>
Cumene	<1	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE LIQUIDS - Category 3          EYE IRRITATION - Category 2A          CARCINOGENICITY (inhalation) - Category 2          SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3</p>
Ethylbenzene	<1	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE LIQUIDS - Category 2          SKIN IRRITATION - Category 2          EYE IRRITATION - Category 2A          CARCINOGENICITY (inhalation) - Category 2          SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3</p>
Naphthalene	≤0.3	<p>ASPIRATION HAZARD - Category 1          FLAMMABLE SOLIDS - Category 2          ACUTE TOXICITY (oral) - Category 4          CARCINOGENICITY - Category 2</p>

### [SARA 313](#)

## Section 15. Regulatory information

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	toluene	108-88-3	<4
	xylene	1330-20-7	<4
	benzene	71-43-2	<1
	ethylbenzene	100-41-4	<1
	naphthalene	91-20-3	<0.4
<b>Supplier notification</b>	toluene	108-88-3	<4
	xylene	1330-20-7	<4
	benzene	71-43-2	<1
	ethylbenzene	100-41-4	<1
	naphthalene	91-20-3	<0.4

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: ETHYL ALCOHOL; DENATURED ALCOHOL; PENTANE; toluene; xylene; HEPTANE; N-HEPTANE
- New York** : The following components are listed: Toluene; Xylene mixed; Benzene; Cumene; Benzene, 1-methylethyl-; Ethylbenzene; Naphthalene
- New Jersey** : The following components are listed: Gasoline
- Pennsylvania** : The following components are listed: E85

### California Prop. 65 Clear and Reasonable Warnings (2018)

**⚠ WARNING:** This product can expose you to chemicals including Ethanol, Benzene, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Cumene, Ethylbenzene, Naphthalene, which are known to the State of California to cause cancer, and Toluene, n-Hexane, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
ethanol	<90	Yes.	Yes.	-	-
toluene	<4	No.	Yes.	-	Yes.
benzene	<1	Yes.	Yes.	Yes.	Yes.
cumene	<1	Yes.	No.	-	-
ethylbenzene	<1	Yes.	No.	Yes.	-
naphthalene	<0.4	Yes.	No.	Yes.	-
n-hexane	<1	No.	Yes.	-	-

### International regulations

#### Inventory list

- United States** : All components are listed or exempted.
- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : Not determined.
- Europe** : All components are listed or exempted.
- Japan** : **Japan inventory (ENCS):** Not determined.  
**Japan inventory (ISHL):** Not determined.
- Malaysia** : Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Thailand** : Not determined.
- Turkey** : Not determined.

## Section 15. Regulatory information

**Viet Nam** : Not determined.

## Section 16. Other information

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
GERM CELL MUTAGENICITY - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), hearing organs) - Category 2	Calculation method
AQUATIC HAZARD (ACUTE) - Category 2	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

### History

**Date of printing** : 8/7/2018

**Date of issue/Date of revision** : 8/7/2018

**Date of previous issue** : No previous validation

**Version** : 1

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 UN = United Nations

**References** : Not available.

☑ Indicates information that has changed from previously issued version.

### Notice to reader



## Section 16. Other information

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation