

**MYSTIK® PRECISION BLUE®  
MARINE GEAR LUBRICANT**



Date 01/04

**For API Gear Lubricant Service: GL-3, GL-4, GL-5 + LS, GL-6**

**DESCRIPTION:**

Mystik® Precision Blue® Marine Gear Lubricant SAE 80W-90 provides maximum protection against rust, corrosion, deposits, and wear. The SAE 80W-90 viscosity grade makes it the primary lubrication choice for most of the lower gear case units manufactured today. It is recommended for use in any outboard gear case or inboard/outboard stern drive which specifies an SAE 80W-90 or SAE 90 viscosity grade.

**FEATURES:**

- Formulated specifically for the marine industry
- Designed to provide maximum protection against rust, corrosion, deposits, and wear
- Recommended for use in any outboard gear case or inboard/outboard stern drives which specify an SAE 80W-90 or SAE 90 viscosity
- Multiple viscosity grade with high viscosity index. Wide temperature range for all season application in most climates
- Has outstanding heat resistance, thereby providing longest life at the highest temperatures
- MIL-PRF-2105E Military Specification performance level. Can also be used where MIL-L-2105D/C/B gear lubricant is recommended.
- For API Gear Lubricant Services: GL-3, GL-4, GL-5, GL-5 + LS (add to and/or drain and refill), GL-6
- Mack GO-J and GO-H Gear Oil performance

**CLASSIFICATIONS:**

**TYPICAL PROPERTIES:**

**MYSTIK® PRECISION BLUE® MARINE GEAR LUBRICANT**

<b>Material Code</b>	<b>663715002</b>
SAE Grade	80W-90
AGMA EP Lubricant Number	4 EP
Gravity, ASTM D 4052 @ 60°F, °API	27.9
Pounds/Gallon @ 60°F.	7.4
Specific Gravity @ 60°F.	0.89
Flash Point, COC, ASTM D 92, °F. (°C.)	410 (210)
Viscosities:	
cP @ -15°F.	142,000
cSt. @ 40°C.	143.7
cSt. @ 100°C.	16.43
cSt. (SUS) @ 100°F.	161.5 (749)
cSt. (SUS) @ 210°F.	16.94 (85.7)
Viscosity Index	121
Pour Point, ASTM D 97, °F. (°C.)	-20 (-29)
Appearance, Color	Blue

**RECOMMENDED FOR USE IN:**

<b>MAKE</b>	<b>MODEL</b>	<b>YEAR</b>
AEROMARINE	5, 7.5, 9 HP	1970-1971
BEARCAT, INC.	55 HP	1963-1973
CHRYSLER	85 HP	1970-1973
	3.6 HP	1970-1972
	4 THROUGH 150 HP	1971-1984
CLINTON	9 HP	1978-1985
ESKA	1.2 THROUGH 15 HP	1963 & LATER
EVINRUDE	ALL	1973 & LATER
FORCE/US MARINE	ALL	1985 & LATER
FOREMOST	3.5, 6, 92 HP	1966
HONDA (FOUR-STROKE)	ALL	1977 & LATER
JOHNSON	ALL	1973 & LATER
MARINER	2 THROUGH 200 HP	1974 & LATER
McCULLOCH (SCOTT)	MODEL 590/630	
	7.5, 33, 40, 43.7, 45, 60, 75, 75.2 HP	1963-196
	9 HP	1967
	12, 14, 14.1, 16, 22, 25, 27, 28 HP	1963-1967
MERCURY	3.9 THROUGH 300 HP	1963 & LATER
NEPTUNE MIGHTY MITE	2.0 HP	1979 & LATER
NISSAN	ALL	1988 & LATER
SEA KING	2 HP	1983
	3.5, 5 HP	1977-1984
	7.5 THROUGH 15 HP	1977-1984
	2, 4, 9.9, 15 HP	1985 & LATER
SEARS/GAMEFISHER	1.2 THROUGH 15 HP	1977 & LATER
SOLO	6 HP	1987 & LATER
SPIRIT	2 THROUGH 140 HP	1976-1981
SUZUKI	2 THROUGH 200 HP	1975 & LATER
TANAKA/AQUA-BUG	ALL	1986 & LATER
TRITON	4, 5.5, 7.5 HP	1977 & LATER
VOLVO-PENTA	3.9 THROUGH 75 HP	1972-1979
WIZARD	3.5 THROUGH 20 HP	1971-1981
YAMAHA	ALL	1984 & LATER

PLEASE REFER TO OWNER'S MANUAL FOR LUBRICATION RECOMMENDATIONS NOT LISTED ABOVE.