

CITGO SUPERGARD® AIR-COOLED
2-CYCLE ENGINE OIL



Date 03/18

DESCRIPTION: CITGO SUPERGARD Air-Cooled 2-Cycle Engine Oil is a premium performance synthetic blend lubricant designed for use in high performance air-cooled two-stroke engines.

QUALITIES: SUPERGARD Air-Cooled 2-Cycle Engine Oil is engineered for lower smoke and advanced protection for air-cooled 2-cycle engines. This synthetic blend formula meets or exceeds the rigorous requirements of the API TC, JASO FD and ISO-L-EGD classifications for 2-cycle air-cooled engine oils and also exceeds the performance requirements for JASO FC, FB; ISO-L-EGC and -EGB. This advanced oil helps to protect today's high RPM air-cooled 2-cycle engines against exhaust port blocking, combustion chamber and piston deposits, ring sticking and scuffing, and wear. The JASO FD Certification number for this lubricant is 001 CGO 545.

SUPERGARD Air-Cooled 2-Cycle Engine Oil is formulated with premium base oils and a low ash additive package that provides excellent lubricity and detergency performance which surpasses the standard for preventing piston and combustion chamber deposits. In addition, SUPERGARD Air-Cooled 2-Cycle Engine Oil is a synthetic blend which reduces exhaust smoke and prevents piston seizure and cylinder scuffing. SUPERGARD Air-Cooled 2-Cycle Engine Oil mixes readily with fuel for pre-mix type, even at low temperatures. Consult owners manual for Fluid Specification.

APPLICATIONS: CITGO SUPERGARD Air-Cooled 2-Cycle Engine Oil is recommended for use in air-cooled, 2-cycle applications where an API TC, JASO FD or ISO-L-EGD product is preferred. This oil supercedes previous JASO and ISO specifications. It can be used in either premix or oil injection systems up to 50:1 fuel to oil ratios. Do not use in engines requiring an NMMA® TC-W3® product.

SUPERGARD Air-Cooled 2-Cycle Engine Oil can be used in motorcycles, generators, lawnmowers, and hand held power equipment such as leaf blowers, trimmers, and chainsaws operating in hot, dirty, dusty environments and high loads for extended periods. SUPERGARD Air-Cooled 2-Cycle Engine Oil provides the necessary protection to keep your air-cooled 2-stroke cycle engine running cleaner, longer and with less smoke.

TYPICAL PROPERTIES:

CITGO SUPERGARD® AIR-COOLED 2-CYCLE ENGINE OIL

Material Code	621611001
Gravity, ASTM D4052, °API	32.0
Density, lb/gal, at 60°F	7.21
Flash Point, PMCC, ASTM D93, °F (°C)	185 (85)
COG, ASTM D92, °F (°C)	203 (95)
Viscosity, ASTM D445, cSt at 40°C	55
cSt at 100°C	8.5
ASTM D2161, SUS at 100°F	281
SUS at 210°F	54.8
Viscosity Index, ASTM D2270	129
Pour Point, ASTM D97, °F (°C)	-49 (-45)
Appearance, Color	Purple
Sulfated Ash, ASTM D874, %	0.1
Total Base Number, ASTM D2896, mg KOH/g	2.2

CITGO and SUPERGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.