

CITGO TRANSGARD® HEAVY-DUTY TRANSMISSION FLUIDS



Date 04/18

DESCRIPTION: CITGO TRANSGARD Heavy-Duty Transmission Fluids are new generation Allison C-4 and CAT TO-4 transmission and drivetrain fluids. They are designed for heavy-duty construction equipment powershift transmissions, final drives and wet brakes. Compared to engine oil, TRANSGARD Heavy-Duty Transmission Fluids will improve transmission performance and power transfer under conditions of high horsepower output, increased loads, and higher transmission operating temperatures associated with heavy equipment. Base stocks and additives are carefully selected for compatibility with clutch face and seal materials.

Available Viscosity Grades: 10W, 30, 50 and 60.

QUALITIES: CITGO TRANSGARD Heavy-Duty Transmission Fluids provide longer transmission life than heavy-duty engine oils.

In meeting Allison C-4 (SAE 10W and 30 grades), Komatsu Micro-Clutch and Caterpillar TO-4 requirements, CITGO TRANSGARD Heavy-Duty Transmission Fluids offer improved performance while allowing product consolidation. They are offered in four viscosity grades to meet summer and winter powershift requirements. CITGO TRANSGARD Heavy-Duty Transmission Fluids' compatibility with asbestos-free clutch materials offers extended clutch life. Due to their physical and chemical properties, TRANSGARD Heavy-Duty Transmission Fluids provide greater power transfer efficiency. These fluids are recommended for lubrication of winch, clutch plates, gears and bearings. They will help reduce brake chatter in wet brake applications.

APPLICATIONS: Formulated to meet the performance requirements of:

- Allison C-4 – SAE 10W and 30 grades
- Caterpillar TO-4, CD/TO-2 – all grades
- Komatsu Micro-Clutch – all grades

BENEFITS: Use of CITGO TRANSGARD Heavy-Duty Transmission Fluids pay big dividends through reduced maintenance costs, longer equipment life, reduced downtime and higher production output. These are provided through reduced gear wear, improved friction control and greater rimpull. Rust and corrosion control protects gear cases and drive trains under the most severe conditions. The SAE 60 grade provides the greatest fluid film thickness for wear protection during severe operation.

(Continued)

CITGO TRANSGARD® HEAVY-DUTY
TRANSMISSION FLUIDS



Date 04/18 - (Continued)

TYPICAL PROPERTIES:

CITGO TRANSGARD® HEAVY-DUTY TRANSMISSION FLUIDS

SAE Grade	10W	30	50	60
Material Code	633321001	633323001	633325001	633326001
Gravity, ASTM D4052, °API	31.1	31.0	27.3	25.2
Density, lbs./gallon	7.30	7.37	7.49	7.51
Flash Point, COC, ASTM D92, °F (°C)	420 (216)	446 (230)	511 (266)	532 (278)
Viscosity, ASTM D445, cSt at 40°C	38.1	96	209	330
Viscosity, ASTM D445, cSt at 100°C	6.3	11.3	18.8	25.5
Viscosity Index, ASTM D2270	112	104	100	100
Brookfield Apparent Viscosity, ASTM D2983, cP, at Temp, °C	23,000 -35	80,000 -25	45,000 -15	139,500 -15
Pour Point, ASTM D97, °F (°C)	-38 (-39)	-27 (-33)	+5 (-18)	0 (-18)
Color, ASTM D1500	L3.0	L3.5	4.0	L7.0

CITGO and TRANSGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.