



# CITGO<sup>®</sup> Lithoplex<sup>®</sup> MP Greases

## OVERVIEW



- Versatile extreme pressure (EP) lithium complex greases.
- Dependable performance in a broad range of applications.
- Excellent performance over a wide temperature range.
- Formulated for long life.

## FEATURES & BENEFITS



- Extremely stable lithium complex formula retains its consistency even in the most severe service.
- EP and anti-wear additives provide protection under severe conditions.
- Corrosion resistance protects and extends equipment life.
- Oxidation resistance extends grease life and protects equipment for longer periods.
- Lithoplex MP 1 and MP 2 greases meet the ASTM D4950 requirements for Wheel Bearing Category GC and Chassis Lubrication Category LB.




## APPLICATIONS



- Satisfy a wide range of industrial and automotive applications.
- Particularly suitable for bearings, ball joints, and bushings.
- Refer to equipment owner's manual for proper lubricant recommendation.

## PROPERTIES



## Typical Properties for CITGO Lithoplex MP Greases:

Material Code	655342001	655341001	655340001
NLGI Grade	0	1	2
Thickener Type	Lithium Complex	Lithium Complex	Lithium Complex
Color	Gray	Gray	Gray
Texture	Smooth, Adhesive	Smooth, Adhesive	Smooth, Adhesive
Worked Penetration, ASTM D217	355-385	310-340	265-295
Dropping Point, ASTM D2265, °F(°C)	—	500 (260)	530 (277)
Rust Prevention, ASTM D1743	Pass	Pass	Pass
Water Washout, ASTM D1264, % Loss @ 175°F	8.3	5.0	2.0
Four-Ball Wear, ASTM D2266, mm	0.50	0.45	0.45
Four-Ball Weld, ASTM D2596, kgf	315	315	315
Four-Ball Load Wear Index, ASTM D2596, kgf	55	58	58
Base Oil Viscosity @ 40°C, cSt	230	230	230
NLGI Certified, ASTM D4950	—	GC-LB	GC-LB

CITGO and Lithoplex are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.