

CITGO SUPERGARD® MARINE PLUS GREASE



Date 03/18

DESCRIPTION: CITGO SUPERGARD Marine Plus Grease is a smooth but tacky blue grease with outstanding water resistance. It is designed to provide excellent lubrication for greased chassis points and other wet-environment applications.

QUALITIES: SUPERGARD Marine Plus Grease combines an anhydrous calcium thickener, special polymer, and proprietary additive system to ensure superior performance in freshwater marine applications.

- Excellent water resistance
- Includes rust, corrosion and wear protection
- Extreme Pressure (EP), shock load and fretting wear (vibration) protection
- Compatible with commonly used lithium, lithium complex and anhydrous calcium based greases
- Polymer fortified for very good metal adhesion

APPLICATIONS: Recommended for marine applications including greased chassis points, boat lifts, etc. Lubricates well over a wide temperature range up to 250° F. It is not recommended for automotive disc brake wheel bearings. CITGO SUPERGARD Marine Plus Grease is also an excellent choice in non-marine applications where a general purpose EP grease with outstanding water resistance is desired, such as water pumps, fifth wheels and other equipment operating in wet conditions.

Consult owner’s manual for proper lubricant selection.

TYPICAL PROPERTIES:

CITGO SUPERGARD® MARINE PLUS GREASE

NLGI Grade	2
Material Code	655707001
Thickener Type	Anhydrous Calcium
Texture	Smooth, Adhesive
Color, Observed	Blue
Worked Penetration, ASTM D217	265-295
Dropping Point, ASTM D566, °F (°C)	290 (143)
Oil Separation, ASTM D1742, % loss	1
Rust Prevention, ASTM D1743, rating	Pass
Oxidation Stability, ASTM D942, psi drop @ 100 hrs.	5
Timken OK Load, ASTM D2509, lb.	50
Four-Ball Wear, ASTM D2266, mm	0.6
Approximate Temperature Range, °F (°C)	0 to 250 (-18 to 121)
Viscosity: 40°C, cSt	1080

CITGO and SUPERGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.