




# CITGO® Pacemaker® SD Oils

## OVERVIEW




- High-quality circulating lubrication oils specifically designed for steel mill applications, with superior oil/water separation characteristics, oxidation stability, and rust and corrosion protection. Available in viscosity grades 220, 320, 460, and 680.
- Exceed Siemens AG requirements for Morgoil® Advanced Bearing Lubricant 'Super Demulsibility' specification.

## FEATURES & BENEFITS




- Outstanding water removal characteristics.
- Long service life in circulating systems.
- Corrosion protection and foam control.
- Excellent filterability.
- Deposit control.

## APPLICATIONS



- Recommended for circulating systems requiring AGMA R&O type lubricants and operating in severe conditions, such as water contamination. These products allow rapid oil separation from water at steel mill operating temperatures, especially in Siemens AG (formerly Morgan Construction Company) steel mill roll bearings.
- Can be used as:
  - Gear oils
  - Compressor oils
  - Rust- and oxidation-inhibited (R&O) oils
  - Roll bearing lubricants (blooming, slabbing, hot and cold strip mills)
  - Morgoil® lubrication system oils
  - MESTA® system oils

Morgoil and MESTA are registered trademarks of Siemens AG.

**PROPERTIES****Typical Properties for CITGO Pacemaker SD Oils:**

<b>Grade</b>	<b>220</b>	<b>320</b>	<b>460</b>	<b>680</b>
Material Code	633044001	633045001	633047001	633050001
Gravity, ASTM D4052, °API	30.0	29.3	26.9	26.6
Density, lb/gal	7.30	7.33	7.44	7.45
Flash Point, ASTM D92, COC, °F (°C)	464 (240)	464 (240)	554 (290)	592 (311)
Viscosity, ASTM D445				
cSt at 40°C	220	320	460	680
cSt at 100°C	22.8	29.2	30.8	42.2
Viscosity Index, ASTM D2270	126	123	96	102
Pour Point, ASTM D97, °F (°C)	-6 (-21)	-6 (-21)	16 (-9)	16 (-9)
Color, ASTM D1500	L2.0	L3.0	L5.0	L5.0
Rust Test, A, ASTM D665	Pass	Pass	Pass	Pass
Demulsibility, ASTM D2711 (ml Emulsion at 125°F)	1.0 max.	1.0 max.	1.0 max.	1.0 max.
Water Separation at 180°F, ASTM D1401	40-40-0 (15)	40-40-0 (15)	40-40-0 (20)	40-40-0 (25)
Foam Test, ASTM D892, Seq. I, II, III	Pass	Pass	Pass	Pass
AGMA Grade	5	6	7	8

CITGO and Pacemaker are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.