

CITGO PACEMAKER® GAS ENGINE OIL 935



Date 06/15

**DESCRIPTION:** CITGO Pacemaker Gas Engine Oil 935 is a non-detergent stationary natural gas enzyme oil fortified with ashless inhibitors to resist oxidation, corrosion and foaming. It is available in a single viscosity grade at the point where the SAE 30 and SAE 40 grades meet.

**QUALITIES:** CITGO Pacemaker Gas Engine Oil 935 is formulated with high viscosity index base stocks combined with an excellent high-temperature ashless oxidation inhibitor to produce a non-detergent oil with exceptional thermal stability and low carbon residue.

**APPLICATIONS:** CITGO Pacemaker Gas Engine Oil 935 is recommended where a non-detergent oil is specified. Its principal applications are in 4-cycle horizontal engines, 2- and 4-cycle engines equipped with Fuller's earth by-pass filters, and in naturally-aspirated 2-cycle engines equipped with full flow filters. This product can also be used to lubricate compressor cylinders in natural gas service.

**TYPICAL PROPERTIES:**

**CITGO PACEMAKER® GAS ENGINE OIL 935**

<b>SAE Grade</b>	<b>30/40</b>
Material Code	632030001
Gravity, ASTM D 4052, °API	30.2
Pounds Per Gallon	7.29
Flash Point, ASTM D 92, COC, °F (°C)	518 (270)
Fire Point, ASTM D 92, COC, °F (°C)	530 (277)
Viscosity, ASTM D 445, cSt at 40°C	114
cSt at 100°C	12.4
ASTM D 2161, SUS at 100°F	596
SUS at 210°F	69
Viscosity Index, ASTM D 2270	99
Pour Point, ASTM D 97, °F(°C)	10 (-12)
Color, ASTM D 1500	L0.5
Carbon Residue, % (base stock)	0.02
Total Acid No., ASTM D 664	0.1
Total Base No., ASTM D 2896	0.2
Oxidation Inhibitor	Yes
Foam Suppressor	Yes

CITGO and Pacemaker are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.