



CITGO[®] Pacemaker[®] HV Oils

OVERVIEW




- High-quality petroleum fluids with high boiling range and low vapor pressure, designed especially for use in high-vacuum pump applications where a high-quality mineral oil is required.

FEATURES & BENEFITS




- High initial boiling points and low vapor pressures.
- Produced with special processes and quality assurance procedures to help ensure excellent vacuum pump performance.
- Inherently high oxidation resistance, thermal stability, and low chemical reactivity.
- Special product handling assures very low moisture and volatiles contamination that could adversely affect vapor pressure characteristics.

APPLICATIONS



- CITGO Pacemaker HV-39 is designed for direct-drive vacuum pumps such as Welch, Yellow Jacket, Precision, Leybold-Heraeus, Edwards and Alcatel, where lower viscosity vacuum pump oil is required to prevent heat build-up, provide high ultimate vacuum, and handle high-vacuum pump speeds.
- Pacemaker HV-68 is designed for belt-driven vacuum pumps such as Welch and Cenco.
- Note: Keep containers of CITGO Pacemaker HV Oils tightly sealed and stored in areas that do not have wide variations in temperature.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for CITGO Pacemaker HV Oils:

Grade	HV-39	HV-68
Material Code	634104001	634105001
Gravity, ASTM D4052, °API	31.7	32.3
Density, lb/gal at 60°F	7.22	7.2
Flash Point, COC, ASTM D92, °F (°C)	435 (224)	465 (241)
Viscosity, ASTM D445		
cSt at 40°C	42	68
cSt at 100°C	6.4	9.2
Viscosity, ASTM D2161		
SUS at 100°F	196	315
SUS at 200°F	47	57
Viscosity Index, ASTM D2270	101	113
Pour Point, ASTM D97, °F (°C)	0 (-18)	0 (-18)
Color, ASTM D1500	L0.5	L0.5
Neutralization No., ASTM D974, mg KOH/ml	<0.05	<0.05
Copper Corrosion, ASTM D130, 3 hours at 100°C	1A	1A
Carbon Residue, ASTM D4530, wt %	<0.01	<0.02
Vapor Pressure, ASTM D5190, Torr. @ 100°F (37°C)	0.00025	0.00065

CITGO and Pacemaker are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.