



CITGO PRESS OIL 68

Date 04/18

**DESCRIPTION:** CITGO Press Oil 68 is formulated with premium, highly refined base oils, a unique selection of performance additives, and synthetic components to meet the demanding gear and bearing lubrication requirements found in printing press systems.

- BENEFITS:**
- Provides extreme pressure and antiwear protection on gears and bearings.
  - Exhibits outstanding thermal and oxidative stability.
  - Provides rust and corrosion protection.
  - Prevents sticking of eccentrics.
  - Offers increased gear protection against shock loading and wear.
  - Contains inhibitors to minimize foaming and air entrainment.
  - Provides excellent adhesion and cohesion on metal parts.
  - Extends fluid service life with a balanced additive system to handle severe press operating conditions.
  - Contains no heavy metals.
  - Offers improved viscosity control, minimum viscosity shear.

**APPLICATIONS:** CITGO Press Oil 68 is recommended for service for high speed gearing and bearing applications found in the printing industry. CITGO Press Oil 68 exceeds the performance requirements of Goss SBM 5078 and Man Roland Presses.

**CITGO PRESS OIL 68**

Grade	68
Material Code	633821001
Gravity, ASTM D4052, °API	29.2
Density, lb/gal	7.33
Flash Point, (COC), ASTM D92, °F (°C)	439 (226)
Viscosity, ASTM D445, cSt at 40°C	68.1
100°C	10.28
ASTM D2161, SUS at 100°F	320
210°F	62
Viscosity Index ASTM D2270	117
Pour Point, ASTM D97, °F (°C)	-27 (-33)
Color, ASTM D1500	L2.5
Copper Corrosion, 3 hr at 100°C, ASTM D130	1A
Rust Test, D665 A, B	Pass
Four Ball Wear at ASTM D4172, 40 kg, mm	0.36
Four Ball Wear Index, ASTM D2783	55.5
Four Ball Wear, Index (Weld Point), Kg	250
Timken OK Load, ASTM D2782, lb.	50
Foam Test, Seq. I, ml	0-0
Seq. II, ml	50-0
Seq. III, ml	0-0
Tackifier	Yes

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.