




CITGO® Gascom® R Oil

OVERVIEW




- Formulated to satisfy the lubrication requirements of gas compressors used for wet, scrubbed, or processed gases.

FEATURES & BENEFITS




- High viscosity index base stocks and special lubricity additives reduce lubricant displacement by water and/or liquid hydrocarbons.
- Tolerates a wide variety of gas quality.

APPLICATIONS



- Recommended for single- or double-acting reciprocating compressors in raw, scrubbed, or processed natural gas service.
- Can be used as a mild stamping and drawing lubricant where enhanced lubricity is needed.

PROPERTIES



Typical Properties for CITGO Gascom R Oil:

ISO VIS Grade	220
Material Code	637142001
Specific Gravity, 60°/60°F	0.8838
Gravity, ASTM D4052, °API	28.6
Flash Point ASTM D92, °F (°C)	450 (232)
Viscosity ASTM D445	
cSt at 40°C	234
cSt at 100°C	20.4
Viscosity ASTM D2161	
SUS at 100°F	1350
SUS at 210°F	100
Viscosity Index, ASTM D2270	100
Pour Point ASTM D97, °F (°C)	5 (-9)
Color, ASTM D1500	4.0

CITGO and Gascom are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.