



CITGO GASCOM® R OIL

Date 06/15

DESCRIPTION: CITGO Gascom R Oil is formulated to satisfy the lubrication requirements of gas compressors used for wet, scrubbed or processed gases.

QUALITIES: CITGO Gascom R Oil is formulated with high VI base stocks and special lubricity additives which reduces lubricant displacement by water and/or liquid hydrocarbons.
CITGO Gascom R Oil can tolerate a wide variety of gas quality.

APPLICATIONS: CITGO Gascom R Oil satisfies the lubricant requirements of single or double-acting reciprocating compressors in raw, scrubbed or processed natural gas service.
CITGO Gascom R Oil can also be used as a mild stamping and drawing lubricant where enhanced lubricity is needed.

TYPICAL PROPERTIES:

CITGO GASCOM® R OIL

ISO VIS Grade	220
Material Code	637142001
Specific Gravity, 60°/60°F	0.8838
Gravity, ASTM D 4052, °API	28.6
Flash Point, ASTM D 92, °F (°C)	450 (232)
Viscosity, ASTM D 445, cSt at 40°C	234
cSt at 100°C	20.4
ASTM D 2161, SUS at 100°F	1350
SUS at 210°F	100
Viscosity Index, ASTM D 2270	100
Pour Point, ASTM D 97, °F (°C)	5 (-9)
Color, ASTM D 1500	4.0

CITGO and Gascom are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.