



CITGO JET LUBRICANT TM

Date 09/16

DESCRIPTION: CITGO Jet Lubricant TM is a quality soap-thickened petroleum resin based compound for use as a Traction Motor Gear Lubricant in heavy duty, high speed locomotive gear boxes. It provides an adhesive film that protects gears under heavy loads.

QUALITIES: CITGO Jet Lubricant TM is formulated from petroleum resins to ensure good adhesion. CITGO Jet Lubricant TM is available in drums and in one pound polyethylene bags for ease of application.

APPLICATIONS: CITGO Jet Lubricant TM is an excellent lubricant for various open and closed gear cases and certain slow moving open gears used throughout the industry.

GE Specification D50 E8C

Consult owner's manual for proper lubricant selection.

TYPICAL PROPERTIES:

CITGO JET LUBRICANT TM

Material Code	655780001
Soap Type	Sodium
Texture	Tacky
Color	Dark Brown
Brookfield Viscosity, cP at 200°F	5,000 - 10,000
Timken OK Load, ASTM D2509, lbs	40
Four Ball EP Weld, ASTM D2596, kgf	250
Load Wear Index, ASTM D2596	38

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.