



CITGO® Compressor Oils 35LP and 45LP

OVERVIEW




- High-quality, non-foaming, non-detergent compressor cylinder lubricants engineered for the requirements of air and gas compressors and older stationary natural gas engines that utilize activated clay filtration.

FEATURES & BENEFITS




- High viscosity index paraffinic base stocks with superior viscosity-temperature characteristics.
- Additives inhibit oxidation, rust, and corrosion.
- Good demulsibility characteristics.
- Low pour point for cold-climate operations.
- Low carbon-forming tendency, along with oxidation resistance, minimizes exhaust valve deposits.

APPLICATIONS



- Recommended for cylinder lubrication in reciprocating air and natural gas compressors.

PROPERTIES**Typical Properties for CITGO Compressor Oils 35LP and 45LP:**

	35LP	45LP
Material Code	633746001	633748001
Gravity, ASTM D4052, °API	29.2	30.98
Density, lbs/gal	7.284	7.25
Flash Point, ASTM D92, °F (°C)	554 (290)	475 (246)
Viscosity ASTM D445		
cSt at 40°C	115	171
cSt at 100°C	12.3	19.0
Viscosity Index D2270	97	126
Pour Point ASTM D97, °F (°C)	-17 (-27)	-27 (-33)
Color, ASTM D1500	L2.0	L0.5
Total Acid No. mgKOH/g, ASTM D664	0.1	0.23
Foam Test, ASTM D892		
Seq. I, mL	0-0	0-0
Seq. II, mL	0-0	0-0
Seq. III, mL	0-0	0-0
RPVOT, Oxidation, ASTM D2272, minutes	320	525

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.