



CITGO® CITGEAR® HD Synthetic Gear Lubricants

OVERVIEW



- State-of-the-art heavy duty, synthetic gear and bearing lubricants designed for use in manual transmissions, transfer cases, and differentials of passenger cars, trucks, farm tractors, construction equipment, and over-the-road trucks.
- Formulated using a unique, proprietary combination of synthetic base stocks and additives to offer maximum protection for gears and bearings over a wide range of operating temperatures.

FEATURES & BENEFITS



- Superior oxidation resistance for extended drain intervals.
- Excellent load-carrying properties (SAE 75W-90, 75W-140, and 80W-140) for maximum protection.
- High viscosity index and low pour point synthetic base stocks provide reduced friction, resulting in fuel economy potential during low-temperature start-ups or operating conditions.
- Excellent demulsibility, hydrolytically stable, and non-foaming.
- Shear-resistant for lasting viscosity performance.

APPLICATIONS



- **SAE 75W-90, 75W-140, and 80W-140 grades** are recommended for differentials (including limited-slip units), non-synchronized manual transmissions for which hypoid-type lubricants are required, and transfer cases for heavy equipment: trucks, tractors, industrial gear drives, automobiles, and farm machinery.

Meet or exceed the following performance requirements:
API Service Classification GL-5 and MT-1

- **SAE 50** grade is recommended for heavy duty service in manual transmissions for which the manufacturer normally recommends either engine oils or GL-1 to GL-4 lubricants. Contains anti-wear protection and rust, oxidation, foam, and corrosion inhibitors to protect bearings and synchronizers and to promote longer transmission life. Provides improved start-up, easier shifting, and less gear wear in low-temperature environments. Less friction, less drag, and improved oxidation resistance combine to provide fuel economy benefits and longer drain intervals.

Recommended in applications calling for the following specifications:
API GL-4, MT-1

PROPERTIES**Typical Properties for CITGO CITGEAR HD Synthetic Gear Lubricants:**

SAE Grade	75W-90	75W-140	80W-140	50
Material Code	632496001	632497001	632498001	632495001
Specific Gravity	0.865	0.869	0.867	0.857
Density, lb/gal	7.20	7.23	7.22	7.14
Viscosity, ASTM D445,				
cSt at 40°C	126	185	211	137
cSt at 100°C	16.7	25.8	25.1	17.9
Viscosity Index, ASTM D2270	144	171	150	145
Brookfield Viscosity ASTM D2983				
cP at -26°C	—	—	46,300	28,800
cP at -40°C	114,500	137,500	—	—
Pour Point ASTM D97, °F (°C)	-65 (-54)	-60 (-51)	-36 (-32)	-38 (-39)
Flash Point, ASTM D92, °F (°C)	378 (192)	370 (188)	428 (220)	507 (264)
Foam Test, ASTM D892	Pass	Pass	Pass	Pass
Copper Corrosion, ASTM D130	1A	1A	1A	1A
FZG, Failure Stage	>12	>12	>12	NA

NA = Not Applicable

CITGO and CITGEAR are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.