



CITGO AR SLUSHING OIL

Date 04/18

DESCRIPTION: CITGO AR Slushing Oil is a light colored, low viscosity rust preventative coating oil. It utilizes a highly effective metal protection system to provide excellent rust protection for steel stored for intermediate periods under cover. The light viscosity promotes complete surface coverage and quick drainage of excess oil. The low pour point facilitates cold weather storage and handling.

TYPICAL PROPERTIES:**CITGO AR SLUSHING OIL**

Material Code	639760001
Gravity, °API ASTM D4052	32.3
Density, lb/gal	7.19
Flash Point ASTM D93, PM	360
Flash Point ASTM D92, COC	392
Fire Point ASTM D92, COC	437
Viscosity ASTM D445	
cSt at 40°C	18
cSt at 100°C	3.8
Viscosity ASTM D2161	
SUS at 100°F	95
SUS at 210°F	39
Viscosity Index ASTM D2270	98
Carbon Residue ASTM D189, WT%	0.04
Color, ASTM D1500	0.5
Pour Point ASTM D97, °F	-35
Copper Corrosion ASTM D130	1A
Rust Test ASTM D665B, Salt Water	Pass
Humidity Cabinet Test ASTM D1748, hrs.	900+

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.