

CITGO AR Slushing Oil

OVERVIEW




- A light-colored, low-viscosity rust preventative coating oil.

FEATURES & BENEFITS




- Utilizes a highly effective metal protection system to provide excellent rust protection for stored steel.
- Light viscosity promotes complete surface coverage and quick drainage of excess oil.
- Low pour point facilitates cold weather storage and handling.

APPLICATIONS



- Recommended for prevention of rust on steel stored for intermediate periods under cover.

PROPERTIES



Typical Properties for CITGO AR Slushing Oil:

Material Code	639760001
Gravity, °API ASTM D4052	32.3
Density, lb/gal	7.19
Flash Point ASTM D93, PM	360
Flash Point ASTM D92, COC	392
Fire Point ASTM D92, COC	437
Viscosity ASTM D445	
cSt at 40°C	18
cSt at 100°C	3.8
Viscosity ASTM D2161	
SUS at 100°F	95
SUS at 210°F	39
Viscosity Index ASTM D2270	98
Carbon Residue ASTM D189, WT%	0.04
Color, ASTM D1500	0.5
Pour Point ASTM D97, °F	-35
Copper Corrosion ASTM D130	1A
Rust Test ASTM D665B, Salt Water	Pass
Humidity Cabinet Test ASTM D1748, hrs.	900+

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.