

CITGO SUPERGARD® MARINE PLUS  
LOWER UNIT GEAR LUBRICANT



Date 03/18

- DESCRIPTION:** CITGO SUPERGARD Marine Plus Lower Unit Gear Lubricant is formulated specifically for the marine industry. It contains the latest generation of proprietary EP additives, designed to provide maximum protection against wear, rust, corrosion and deposits. It is also guaranteed to protect OEM lower unit warranties.
- QUALITIES:** This improved gear lubricant, specifically designed for boating applications, offers unmatched protection, surpassing other marine gear lubricants using GL-4 and GL-5 80W-90 technology:
- Superior EP lubrication and corrosion protection in the presence of moisture (fresh and sea water).
  - Improved gear protection for shock load conditions encountered with harsh startup engagement, power reversal, and propeller entanglement.
- APPLICATIONS:** Recommended for use in all outboard and stern drive gear units specifying SAE 90, 80W-90 or 85W-90, including OMC Type "C." Includes MerCruiser, OMC Cobra, Volvo stern drives and Mercury, Evinrude, Johnson, Mariner, Yamaha, Suzuki, and Force outboards. Consult owner's manual for Fluid Specifications.

**TYPICAL PROPERTIES:**

**CITGO SUPERGARD® MARINE PLUS LOWER UNIT GEAR LUBRICANT**

SAE Grade	85W-90
Material Code	631515001
Gravity, ASTM D4052, °API	26.3
Density, lb/gal at 60°F	7.5
Flash Point, ASTM D92, COC, °F (°C)	420 (216)
Viscosity, cSt at 100°C	16.0
Brookfield Viscosity, -23°C, cP	102,000
Pour Point, ASTM D97, °F (°C)	-15 (-26)
Channel Point, °F (°C), Max	-31 (-35)
Color, Visual	Blue
Foam Test, ASTM D892	Pass
Copper Corrosion, 3 hrs at 250°F	Pass

CITGO and SUPERGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.