



# CITGO® Lithoplex® Red MP Grease

## OVERVIEW



- A versatile lithium complex grease.
- Provides long life with extreme pressure (EP) performance.


## FEATURES & BENEFITS



- Extremely stable lithium complex formula retains its consistency even in the most severe service.
- Additives provide excellent EP and anti-wear protection under severe conditions.
- Resists corrosion, thereby extending equipment life -- of particular importance in applications where moisture is present.
- Contains oxidation inhibitors to extend grease life and protect the application for longer periods.
- Meets the ASTM D4950 requirements for Wheel Bearing Grease Category GC and Chassis Grease Category LB. Labels display the NLGI Certification Mark GC-LB for Automotive Wheel Bearing & Chassis Lubricant.




## APPLICATIONS



- Recommended for a wide variety of applications including automotive chassis and wheel bearings, and industrial plain and rolling element bearings.
- Refer to equipment owner's manual for proper lubricant recommendation.

## PROPERTIES



## Typical Properties for CITGO Lithoplex Red MP Grease:

<b>Material Code</b>	<b>655387001</b>
NLGI Grade	2
Thickener Type	Lithium Complex
Color	Red
Texture	Smooth, Adhesive
Worked Penetration, ASTM D217	265-295
Dropping Point, ASTM D2265, °F(°C)	500 (260)
Rust Prevention, ASTM D1743, Rating	Pass
Water Washout, ASTM D1264, % Loss @ 175°F	1.4
Four-Ball Weld, ASTM D2596, kgf	315
Four-Ball Load Wear Index, ASTM D2596, kgf	43
Four-Ball Wear, ASTM D2266, mm	0.43
Base Oil Viscosity @ 40°C, cSt (including oil soluble additives)	205
NLGI Certified, ASTM D4950	GC-LB

CITGO and Lithoplex are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.