

CITGO POWER STEERING FLUID  
WITH STOP LEAK



Date 04/16

**DESCRIPTION:** CITGO Power Steering Fluid with Stop Leak is formulated with high-quality base stocks and additives designed to ensure smooth system operation and revitalize dried, shrunken, and hardened seals. This product helps stop or reduce fluid loss caused by leaky seals and, when used as a preventative maintenance fluid, helps avoid future leaks.

- QUALITIES:**
- Superior cold temperature performance
  - Excellent friction and wear protection
  - Anti-wear agents to protect pump components
  - Antioxidants to prevent sludge formation
  - Anti-foam agents to prevent pump cavitation and steering loss
  - Corrosion inhibitors to protect metal components
  - Wide range of seal compatibility

**APPLICATIONS:** For use where the following fluids are specified: GM 9985010, Chrysler 5931, and Ford M2C33-F. For a complete list of equipment specs, visit [www.citgolubes.com/lubes-advisor](http://www.citgolubes.com/lubes-advisor). Consult the owner’s manual for proper fluid selection.

**TYPICAL PROPERTIES:**

**CITGO CITGO POWER STEERING FLUID WITH STOP LEAK**

Material Code	633313001
Gravity, ASTM D4052, °API	32.9
Pounds Per Gallon	7.15
Flash Point, COC, ASTM D92, °F (°C)	424 (218)
Pour Point, ASTM D97, °F (°C)	-54 (-48)
Viscosity, ASTM D445,	
cSt at 40°C	34.3
cSt at 100°C	6.95
ASTM D2983, cP at -20°C	1,020
cP at -40°C	15,100
Viscosity Index, ASTM D2270	169
Color	Light Amber

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.