



CITGO Power Steering Fluid with Stop Leak

OVERVIEW



- Formulated with high-quality base stocks and additives designed to ensure smooth system operation and revitalize dried, shrunken, and hardened seals.
- Helps stop or reduce fluid loss caused by leaky seals and helps avoid future leaks when used as a preventive maintenance fluid.

FEATURES & BENEFITS



- Superior low-temperature performance.
- Excellent protection against friction and wear.
- Anti-wear agents to protect pump components.
- Antioxidants to prevent sludge formation.
- Anti-foam agents to prevent pump cavitation and steering loss.
- Corrosion inhibitors to protect metal components.
- Wide range of seal compatibility.

APPLICATIONS



- Recommended where the following fluids are specified:
GM 9985010
Chrysler 5931
Ford M2C 195-A
- For a complete list of equipment specs, visit www.citgolubes.com/lubes-advisor.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for CITGO Power Steering Fluid with Stop Leak:**

Material Code	633313001
Gravity, ASTM D4052, °API	32.9
Pounds Per Gallon	7.15
Flash Point, COC, ASTM D92, °F (°C)	424 (218)
Pour Point, ASTM D97, °F (°C)	-54 (-48)
Viscosity, ASTM D445,	
cSt at 40°C	34.3
cSt at 100°C	6.95
Viscosity, ASTM D2983,	
cP at -20°C	1,020
cP at -40°C	15,100
Viscosity Index, ASTM D2270	169
Color	Light Amber

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.