



# CITGO<sup>®</sup> SynDurance<sup>®</sup> Synthetic MTF

## OVERVIEW




- A synthetic lubricant designed for fuel efficiency, extended drain intervals, and severe service in heavy duty commercial vehicle transmissions which do not require an extreme pressure (EP) transmission lubricant.
- Specially formulated to protect higher torque transmissions coupled with increased horsepower engines. Approved for use in Eaton transmissions such as Ultrashift Plus, Fuller Advantage, FR, and RT Series transmissions.
- Replaces SAE 50 transmission fluid, and is for use where SAE 50 weight was recommended.

## FEATURES & BENEFITS




- Uniquely formulated to provide up to 1.5% fuel economy improvement while maintaining excellent shear stability.
- Provides high performance and extended drain capability in transmissions.
- Excellent thermal and oxidation stability resists deposit and sludge formation.
- Advanced additive system provides excellent protection from corrosion, foaming, rust, and wear.
- The use of high viscosity index synthetic base fluids allows SynDurance Synthetic MTF to provide superior high- and low-temperature performance.
- Provides friction retention, friction durability, and excellent shear stability to ensure and maintain smooth transmission operations throughout the extended drain interval.
- Formulated to reduce sump operating temperatures.

## APPLICATIONS



- Recommended where low temperatures, wear, or heat present major problems and a non-EP lubricant is required. Typical usage includes transmissions, transfer cases, and wheel end hubs.
- Recommended commercial vehicle applications include line haul, vocational, off-road, pick-up and delivery, and buses.
- Approved for the following OEM specifications:  
Eaton PS-386 (supersedes PS-164 Rev7)  
Mack TO-A Plus  
Meritor O-81 transfer cases  
Navistar MPAPS B-6816 Type II  
API MT-1
- Also recommended for: Eaton Fuller Transmissions, Volvo iShift Transmissions, Mack mDrive Transmissions, API GL-4 (transmissions) and International TMS 6816 (obsolete), ZF Freedomline (AS-Tronic) Transmissions, Meritor Transmissions (O-81), and Con Met Wheel Ends/Hubs.

**PROPERTIES****Typical Properties for CITGO SynDurance Synthetic MTF:**

<b>Material Code</b>	<b>631817001</b>
SAE Viscosity Grade	75W-90
Gravity, ASTM D4052, °API	34.9
Specific Gravity at 60°F	0.85
Density, lb/gal at 60°F	7.09
Viscosities:	
at -40°, cP	51,900
at 40°C, cSt.	95.1
at 100°C, cSt.	14.8
Viscosity Index	163
Pour Point ASTM D97, °F (°C)	-44 (-42)
Flash Point, ASTM D92, °F (°C)	460 (238)

CITGO and SynDurance are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.