

CITGO TRANSGARD® SYNTHETIC MULTI-VEHICLE LOW-VISCOSITY ATF



Date 08/15

DESCRIPTION: CITGO TRANSGARD Synthetic Multi-Vehicle Low-Viscosity ATF contains the highest quality synthetic base stocks combined with a state of the art additive system to provide superior performance in automatic and powershift transmissions.

- QUALITIES:** Superior oxidation and thermal stability
- Outstanding anti-wear performance for protection of transmission hardware
 - Excellent cold temperature flow properties
 - Compatible with a wide range of seal materials to prevent transmission leaks
 - Can be used in most vehicles
 - Provides inventory optimization (multi-vehicle compatible) without the use of ATF supplements.

APPLICATIONS: CITGO TRANSGARD Synthetic Multi-Vehicle Low-Viscosity ATF is suitable for use where the following products are recommended:

- GM vehicles recommending DEXRON® -III
- DEXRON -VI
- MERCON® LV
- JASO 1A
- Toyota WS
- Honda DW-1
- Nissan/Infiniti Matic S
- Hyundai SP-IV

Do not use CITGO TRANSGARD Synthetic Multi-Vehicle Low-Viscosity ATF in vehicles calling for Type F, MERCON SP, or CVT's. Consult owner's manual for fluid specification.

TYPICAL PROPERTIES:

CITGO TRANSGARD® SYNTHETIC MULTI-VEHICLE LOW-VISCOSITY ATF

Material Code	633137001
Gravity, ASTM D 287, °API	36.8
Density, Pounds Per Gallon	7.05
Flash Point, P.M. D 93, °C	220
Viscosity, 100°C, cSt, D 445	6.0
Brookfield Viscosity @ -40°C	11,900
Color	Red

CITGO and TRANSGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

This is not a licensed GM or Ford product.