19045 CITGO SOLVENT 500



Revision 0 6/ 2 0 19

CITGO Solvent 500 is a water-white, hydrotreated naphtha that is low in aromatics and odor. Its major uses are in lamp oils, oil and gas production and in formulations requiring high flash points. See the SDS for safety/regulatory information.

| Property Description | Units | Specification | Typical Proper | ty ASTM Method |
|----------------------------------|--------|---------------|-----------------|----------------|
| ANILINE POINT | DEGF | | 158 | D-611 |
| API GRAVITY (60/60 F) | | 40-50 | 41.2 | D-287 |
| APPEARANCE | | CLEAR, BRIGHT | PASS | |
| COLOR, SAYBOLT | | 28 MIN | 30 | D-156 |
| CORROSION, 3 HRS @ 212 F | | 1 (B) MAX | 1 (A) | D-130 |
| DENSITY @ 60 F (15.6 C) | LB/GAL | | 6.82 | D-287 |
| DISTILLATION, IBP | DEGF | 390 MIN | 408 | D-86 |
| DISTILLATION, 05% | DEGF | | 420 | D-86 |
| DISTILLATION, 10% | DEGF | | 421 | D-86 |
| DISTILLATION, 50% | DEGF | | 425 | D-86 |
| DISTILLATION, 90% | DEGF | | 440 | D-86 |
| DISTILLATION, 95% | DEGF | | 453 | D-86 |
| DISTILLATION, DP | DEGF | 500 MAX | 472 | D-86 |
| DOCTOR TEST | | NEGATIVE | NEGATIVE | D-235 |
| FLASH POINT (TCC) | DEGF | 168 MIN | 173 | D-56 |
| KAURI-BUTANOL VALUE (KB)KB UNITS | | | 30 | D-1133 |
| POUR POINT | DEGF | | -80 | D-97/5949 |
| REFR. INDEX (TYPICAL@250 | C) | | 1.4444 | D-1218 |
| SPECIFIC GRAVITY (60/60 F) | | | 0.8193 | D-287(cal'd) |
| SULFUR CONTENT | PPM | | <1 | D-5453 |
| WATER | PPM | | 52 | D-6304 |





CITGO Petroleum Corporation 135th Street & New Avenue Lemont, IL 60439 Order desk: 1-800-964-7676

Limitations of Warranty & Liability

Seller warrants its product will meet the specifications listed herein and it has good title to the product, free and clear of all liens and security interests; SELLER MAKES NO OTHER WARRANTY, WHETHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Buyer or user accepts liability for determining if the product is suitable for Buyer's or user's intended use. Any recommendation as to use made by Seller is done so at Buyer's or user's risk.

Buyer shall assume all risk and liability for and shall defend, indemnify, and hold Seller harmless from and against all claims, liabilities, costs, and expenses arising from or connected with the possession, transportation, handling, unloading, storage, processing or use of the product alone or in combination with other substances. Buyer's exclusive remedy and Seller's exclusive liability for damages under contract, tort, strict liability, negligence, or otherwise, shall be limited at Seller's option to the refund of the purchase price or the replacement of the product. In no event shall Seller be liable for incidental, indirect, special, or consequential damages.

Buyer acknowledges receipt of a Material Safety Data Sheet for the product and that the product may require special handling, storage, transportation, treatment or use to comply with applicable safety and environmental standards and will take all necessary action to comply therewith. Buyer further agrees to properly label the product if it is repackaged or resold and pass on all safety information and hazard warnings to its employees, purchasers, and users and their employees.