

Mystik® JT-4® 2-Cycle Premium Outboard Engine Oil

OVERVIEW



- An ashless 2-cycle engine oil designed for carbureted 2-cycle marine engines requiring NMMA TC-W3 oil. Guaranteed to protect marine OEM warranties.

FEATURES & BENEFITS



- Designed for premix-type outboard engines.
- Helps reduce piston ring sticking and scuffing.
- Readily mixes with gasoline.

APPLICATIONS



- Recommended for water-cooled or liquid-cooled 2-cycle engines requiring an NMMA TC-W3®, TC-WII® or TC-W® type oil.
- May be used in many air-cooled 2-cycle engine applications requiring TC-W3 or API Service Category TC.
- Recommended for premix systems.
- Provides protection for gasoline-fueled 2-cycle engines when used at the primary dilution recommended by the original equipment manufacturer.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for Mystik JT-4 2-Cycle Premium Outboard Engine Oil:**

Material Code	663088002
Gravity, ASTM D4052, °API	31.5
Density, lb/gal at 60°F	7.23
Flash Point, PMCC, ASTM D93, °F (°C)	178 (81) ¹
Flash Point, COC, ASTM D92, °F (°C)	197 (92)
Viscosity, ASTM D445	
cSt at 40°C	32
cSt at 100°C	5.9
Viscosity, ASTM D2161	
SUS at 100°C	163
SUS at 210°C	46
Viscosity Index, ASTM D2270	130
Pour Point, ASTM D97, °F (°C)	-28 (-39)
Appearance, Color	Blue/Green
Sulfated Ash, ASTM D874, %	<0.004
Total Base Number, ASTM D2896, mg KOH/g	8.6

NOTE

(1) DOT Combustible Liquid

Mystik and JT-4 are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.