


Mystik[®] LithoPlex[®] Pellet Mill #2 Grease

Formerly known as CITGO[®] Lithoplex PM Grease

OVERVIEW




- Designed to provide outstanding performance in industrial applications.
- Provides excellent protection in severe applications of plain and rolling bearings that operate in mild to high temperatures.

FEATURES & BENEFITS



- This product provides excellent protection in applications where high loads exist.
- Provides superior protection in applications where metal to metal friction exists.
- Polymer fortified for improved adhesion and resistance to water.
- Corrosion inhibitor protects equipment from corrosion.

APPLICATIONS



- Recommended for industrial applications where outstanding wear protection, water resistance, corrosion resistance, and extreme pressure protection are required.
- This product provides excellent protection in severe applications of plain and rolling bearings that operate in mild to high temperatures.
- Recommended for rolling element bearings in pellet mills.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for Mystik LithoPlex Pellet Mill #2:

Material Code	655437002
NLGI Grade	2
Thickener Type	Lithium Complex
Color	Red
Texture	Smooth, Adhesive
Worked Penetration, ASTM D217	265-295
Dropping Point, ASTM D2265, °F(°C)	500 (260)
Rust Prevention, ASTM D1743, rating	Pass
Water Washout, ASTM D1264, % loss @ 100°F	2.5
Four-Ball Wear, ASTM D2266, mm	0.48
Timken OK Load, ASTM D2509, lbs	80
Base Oil Viscosity @ 40°C, cSt	155

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.